

# Safety Data Sheet



## 1. Identification

|                             |  |                         |  |
|-----------------------------|--|-------------------------|--|
| <b>Product Name:</b>        | STRUST QT 2PK FLAT WHT CLEAN METAL PRIMR                                       | <b>Revision Date:</b>   | 7/7/2017   |
| <b>Product Identifier:</b>  | 7780502  | <b>Supersedes Date:</b> | 5/15/2015  |
| <b>Product Use/Class:</b>   | Primer/ Alkyd  |                         |  |
| <b>Supplier:</b>            | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA | <b>Manufacturer:</b>    | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA |
| <b>Preparer:</b>            | Regulatory Department  |                         |  |
| <b>Emergency Telephone:</b> | 24 Hour Hotline: 847-367-7700  |                         |  |

## 2. Hazard Identification

### Classification

### Symbol(s) of Product



### Signal Word

Danger

### Possible Hazards

25% of the mixture consists of ingredient(s) of unknown acute toxicity.

### GHS HAZARD STATEMENTS

|                                     |      |                                      |
|-------------------------------------|------|--------------------------------------|
| Flammable Liquid, category 3        | H226 | Flammable liquid and vapour.         |
| Germ Cell Mutagenicity, category 1B | H340 | May cause genetic defects.           |
| Carcinogenicity, category 1B        | H350 | May cause cancer.                    |
| Skin Sensitizer, category 1         | H317 | May cause an allergic skin reaction. |

### GHS LABEL PRECAUTIONARY STATEMENTS

|                |   |
|----------------|---|
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.        |
| P233           | Keep container tightly closed.  |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.                            |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.   |
| P370+P378      | In case of fire: Use alcohol film forming foam, carbon dioxide, dry chemical, dry sand to extinguish. |
| P403+P235      | Store in a well-ventilated place. Keep cool.  |
| P501           | Dispose of contents/container in accordance with local, regional and national regulations.            |
| P201           | Obtain special instructions before use.   |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.  |
| P405           | Store locked up.  |
| P261           | Avoid breathing dust/fume/gas/mist/vapors/spray.  |

P272 Contaminated work clothing should not be allowed out of the workplace.  
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P321 For specific treatment see label

**GHS SDS PRECAUTIONARY STATEMENTS**

P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P363 Wash contaminated clothing before reuse.

**3. Composition/Information On Ingredients****HAZARDOUS SUBSTANCES**

| <u>Chemical Name</u>                   | <u>CAS-No.</u> | <u>Wt.% Range</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|--|----------------|-------------------|--------------------|-----------------------|
| Talc (Hydrous Magnesium Silicate)      | 14807-96-6     | 10-25             | Not Available      | Not Available         |
| Hydrotreated Light Distillate          | 64742-47-8     | 10-25             | GHS08              | H304                  |
| Naphtha, Petroleum, Hydrotreated Light | 64742-49-0     | 10-25             | GHS08              | H304-340-350          |
| Titanium Dioxide                       | 13463-67-7     | 10-25             | Not Available      | Not Available         |
| Zinc Phosphate                         | 7779-90-0      | 1.0-2.5           | Not Available      | Not Available         |
| n-Nonane                               | 111-84-2       | 1.0-2.5           | GHS07              | H332                  |
| Wollastonite                           | 13983-17-0     | 1.0-2.5           | Not Available      | Not Available         |
| Solvent Naphtha, Light Aromatic        | 64742-95-6     | 0.1-1.0           | GHS07-GHS08        | H304-332-340-350      |
| Methyl Ethyl Ketoxime                  | 96-29-7        | 0.1-1.0           | GHS05-GHS06        | H302-312-317-318-331  |

**4. First-aid Measures**

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

**5. Fire-fighting Measures**

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. No unusual fire or explosion hazards noted. Closed containers may explode when exposed to extreme heat due to buildup of steam. Isolate from heat, electrical equipment, sparks and open flame.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

**6. Accidental Release Measures**

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing.

**STORAGE:** Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Keep away from heat, sparks, flame and sources of ignition. Keep container closed when not in use. Product should be stored in tightly sealed containers and protected from heat, moisture, and foreign materials. Store in a dry, well ventilated place. Keep container tightly closed when not in use. Avoid excess heat. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of NFPA Class II combustible liquids.

## 8. Exposure Controls/Personal Protection

| Chemical Name                          | CAS-No.    | Weight %<br>Less Than | ACGIH TLV-<br>TWA    | ACGIH TLV-<br>STEL | OSHA PEL-TWA         | OSHA PEL-<br>CEILING |
|--|------------|-----------------------|----------------------|--------------------|----------------------|----------------------|
| Talc (Hydrous Magnesium Silicate)      | 14807-96-6 | 25.0                  | 2 mg/m <sup>3</sup>  | N.E.               | N.E.                 | N.E.                 |
| Hydrotreated Light Distillate          | 64742-47-8 | 20.0                  | N.E.                 | N.E.               | N.E.                 | N.E.                 |
| Naphtha, Petroleum, Hydrotreated Light | 64742-49-0 | 20.0                  | N.E.                 | N.E.               | N.E.                 | N.E.                 |
| Titanium Dioxide                       | 13463-67-7 | 15.0                  | 10 mg/m <sup>3</sup> | N.E.               | 15 mg/m <sup>3</sup> | N.E.                 |
| Zinc Phosphate                         | 7779-90-0  | 5.0                   | N.E.                 | N.E.               | N.E.                 | N.E.                 |
| n-Nonane                               | 111-84-2   | 5.0                   | 200 ppm              | N.E.               | N.E.                 | N.E.                 |
| Wollastonite                           | 13983-17-0 | 5.0                   | 1 mg/m <sup>3</sup>  | N.E.               | N.E.                 | N.E.                 |
| Solvent Naphtha, Light Aromatic        | 64742-95-6 | 1.0                   | N.E.                 | N.E.               | N.E.                 | N.E.                 |
| Methyl Ethyl Ketoxime                  | 96-29-7    | 1.0                   | 10 ppm               | N.E.               | N.E.                 | N.E.                 |

### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or in any other circumstances where air purifying respirators may not provide adequate protection.

**SKIN PROTECTION:** Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection. Use gloves to prevent prolonged skin contact.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application. Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

## 9. Physical and Chemical Properties

|                                 |                     |   |           |
|---------------------------------|---------------------|---|-----------|
| <b>Appearance:</b>              | Liquid              | <b>Physical State:</b>                              | Liquid    |
| <b>Odor:</b>                    | Solvent Like        | <b>Odor Threshold:</b>                              | N.E.      |
| <b>Relative Density:</b>        | 1.239               | <b>pH:</b>  | N.A.      |
| <b>Freeze Point, °C:</b>        | N.D.                | <b>Viscosity:</b>                                   | N.D.      |
| <b>Solubility in Water:</b>     | Slight              | <b>Partition Coefficient, n-octanol/<br/>water:</b> | N.D.      |
| <b>Decomposition Temp., °C:</b> | N.D.                | <b>Explosive Limits, vol%:</b>                      | 1.1 - 7.0 |
| <b>Boiling Range, °C:</b>       | -18 - 213           | <b>Flash Point, °C:</b>                             | 37        |
| <b>Flammability:</b>            | Supports Combustion | <b>Auto-ignition Temp., °C:</b>                     | N.D.      |
| <b>Evaporation Rate:</b>        | Slower than Ether   | <b>Vapor Pressure:</b>                              | N.D.      |
| <b>Vapor Density:</b>           | Heavier than Air    |   |           |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**CONDITIONS TO AVOID:** Avoid all possible sources of ignition. Avoid temperatures above 120°F (49°C). Avoid contact with strong acid and strong bases.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalis.

**HAZARDOUS DECOMPOSITION:** By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## 11. Toxicological information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Causes Serious Eye Irritation

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May cause skin irritation. Causes skin irritation. Allergic reactions are possible.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Harmful if inhaled. May cause headaches and dizziness. High vapor concentrations are irritating to the eyes, nose, throat and lungs. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Prolonged or excessive inhalation may cause respiratory tract irritation.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Aspiration hazard if swallowed; can enter lungs and cause damage. Harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010) Contains Calcium Silicate (Wollastonite), which is an IARC 3 Agent "unclassifiable as to carcinogenicity to humans" via inhalation. Inhalation exposure to Calcium Silicate is not anticipated through brush application nor normal use. Calcium Silicate is NOT classified as a carcinogen by NIOSH, ACGIH, NTP nor OSHA. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage.

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

### ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>                   | <u>Oral LD50</u> | <u>Dermal LD50</u> | <u>Vapor LC50</u> |
|----------------|--|------------------|--------------------|-------------------|
| 14807-96-6     | Talc (Hydrous Magnesium Silicate)      | 6000             | N.I.               | 30                |
| 64742-47-8     | Hydrotreated Light Distillate          | >5000 mg/kg Rat  | >2000 mg/kg Rabbit | >5000 mg/L Rat    |
| 64742-49-0     | Naphtha, Petroleum, Hydrotreated Light | >5000 mg/kg Rat  | >3160 mg/kg Rabbit | >4951 mg/L Rat    |
| 13463-67-7     | Titanium Dioxide                       | >10000 mg/kg Rat | 2500 mg/kg         | N.I.              |
| 7779-90-0      | Zinc Phosphate                         | >5000 mg/kg Rat  | N.I.               | N.I.              |
| 64742-95-6     | Solvent Naphtha, Light Aromatic        | 8400 mg/kg Rat   | >2000 mg/kg Rabbit | N.I.              |
| 96-29-7        | Methyl Ethyl Ketoxime                  | 930 mg/kg Rat    | 1100 mg/kg Rabbit  | >4.8 mg/L Rat     |

N.I. - No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components. Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

## 14. Transport Information

|                              | <u>Domestic (USDOT)</u>              | <u>International (IMDG)</u> | <u>Air (IATA)</u> | <u>TDG (Canada)</u>                  |
|------------------------------|--------------------------------------|-----------------------------|-------------------|--------------------------------------|
| <b>UN Number:</b>            | N.A.                                 | 1263                        | 1263              | N.A.                                 |
| <b>Proper Shipping Name:</b> | Paint Products in Limited Quantities | Paint                       | Paint             | Paint Products in Limited Quantities |
| <b>Hazard Class:</b>         | N.A.                                 | 3                           | 3                 | N.A.                                 |
| <b>Packing Group:</b>        | N.A.                                 | III                         | III               | N.A.                                 |
| <b>Limited Quantity:</b>     | Yes                                  | Yes                         | Yes               | Yes                                  |

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

No Information

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| Zinc Phosphate       | 7779-90-0      |

#### Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| n-Nonane             | 111-84-2       |

**16. Other Information****HMIS RATINGS**

Health: 2\*      Flammability: 3      Physical Hazard: 0      Personal Protection: X

**NFPA RATINGS**

Health: 2      Flammability: 3      Instability: 0

VOLATILE ORGANIC COMPOUNDS, g/L: 466

SDS REVISION DATE: 7/7/2017

REASON FOR REVISION: Product Composition Changed  
Substance and/or Product Properties Changed in Section(s):  
01 - Identification  
02 - Hazard Identification  
05 - Fire-fighting Measures  
09 - Physical & Chemical Properties  
14 - Transport Information  
15 - Regulatory Information  
16 - Other Information  
Statement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.