

SECTION 1 – IDENTIFICATION				
PRODUCT NAME:	Permanox Flat			
PRODUCT NUMBER:	EV233-00			
PRODUCT CLASS:	Latex Paint			
COLOR:	White			
<b>REVISION DATE:</b>	1/25/2018			
COMPANY IDENTIFICATION: STREET ADDRESS: TELEPHONE #: WEBSITE:	Tibbetts Newport Corp. 2337 S. Birch Street, Santa Ana, CA 92707 (714) 546-6661 (Hours: Monday-Friday from 6:30AM – 3:00PM PST) www.tibbettspaint.com			
IN CASE OF EMERGENCY:	CHEMTREC 800-424-9300 CHEMTREC (Outside US) 1+703-527-3887			

## **RECOMMENDED USE:**

### SECTION 2 - HAZARDS IDENTIFICATION

## **Classification of Substance or Mixture**

This product is NOT hazardous according to 29 CFR 1910.1200 Hazard Communication

GHS Label Elements Hazard Pictograms:	No Symbol
Signal Word:	None
GHS Class:	None
Hazard Statements:	None
Precautionary Stateme	ents: None

# SECTION 3 - COMOSITON/INFORMATION ON INGREDIENTS

Hazardous materials are disclosed according to the GHS requirements. Components not listed are either non-hazardous or are below reportable limits.

Ingredient	CAS No.	Approximate Weight %	
Acrylic Polymer	N/A	15-25	
Titanium Dioxide	13463-67-7	0-20	

SECTION 4 – FIRST AID MEASURES			
Description of Necessary Measures			
Skin Contact:	Wash with soap and water thoroughly. Seek medical attention if irritation develops.		

Eye Contact:

Rinse with water for several minutes. Seek medical attention if irritation develops.

Inhalation:	If breathing is difficult, move person to fresh air and keep at rest in comfortable breathing position. Call a physician if symptoms develop or persist.
Ingestion:	Rinse mouth. If ingestion of large amount occurs, call a poison control center immediately. Do not induce vomiting.

**Most important symptoms and effects, both acute and delayed** Most important known symptoms are detailed in Section 2 and Section 11.

## Indication of any immediate medical attention and special treatment needed No Data Available

	SECTION 5 – FIRE FIGHTING MEASURES				
Suitable Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water Fog, CO <sub>2</sub> , Dry Chemical, Alcohol Resistant Foam.				
Special Hazards:	Carbon oxides				
Advice for firefighters:	Follow recommended procedures in handling fire areas. Wear fire-fighting equipment and self-contained breathing apparatus. If possible, move containers out of the fire area. Cool containers with water spray.				
Further Information:	Pressure may build inside the container.				
SEC	TION 6 – ACCIDENTAL RELEASE-MEASURES				
Personal Precautions:	Use proper personal protective equipment including respirators, goggles, chemical resistant gloves, coveralls. Avoid breathing vapors, mist, or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate all personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.				
Environmental Precautions:	Prevent further leakage or spillage if safe to do so. Do not let product enter drains and waterways.				
Methods for clean-up:	Soak up with inert absorbent material such as sand or saw dust then place in chemical waste container.				
	SECTION 7 – HANDLING AND STORAGE				
Precautions for Safe Handling:	Use with adequate ventilation. Avoid breathing excess vapors and prevent contact with eyes, skin, and clothing.				
Conditions for Safe Storage:	Store in a cool, dry, well-ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed.				
SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION					
Engineering Controls:	Ensure adequate ventilation, especially in confined areas. When ventilation is insufficient to control airborne levels, equip personal protective equipment which meets the OSHA standards.				
Personal Protective Equipment Eye/Face Protection: Skin Protection: Respiratory Protection:	Wear splash goggles or face shields which are approved by NIOSH. Handle with protective chemical resistant gloves. If air-purifying respirators are appropriate, use respirators and components tested and approved by NIOSH.				

# **Hygiene Measures:** Avoid contact with skin, eyes, and clothing. Remove and wash contaminated

clothing before re-use. Wash thoroughly after handling.

**Control Parameters:** 

Chemical Name	CAS No.	Weight%	Cal-OSHA PEL TWA	OSHA PEL TWA	ACGIH TWA
Titanium Dioxide	13463-67-7	0-20%	5 mg/m3 (Respirable Dust)	15 mg/m3	10 mg/m3

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES			
Physical State:	Liquid		
Color:	White		
Odor:	Slight		
Odor Threshold:	Not Available		
Density (lbs/gal):	10.0 - 11.0		
pH:	8-9		
VOC Less Water (g/L):	Less than 50		
<b>Boiling Point (F):</b>	No Data		
Freezing Point (F):	No Data		
Flash Point (F):	No Data		
<b>Evaporation Rate:</b>	Slower than ether		
<b>Upper Explosion Limit:</b>	No Data		
Lower Explosion Limit:	No Data		
Vapor Pressure:	Not Available		
Vapor Density:	Heavier than air		
Solubility in Water:	Soluble		
<b>Partition Coefficient:</b>	Not Available		
Auto-Ignition Temp:	Not Available		
<b>Decomposition Temp:</b>	Not Available		
Viscosity (KU):	95-105		

## SECTION 10 - STABILITY AND REACTIVITY

Reactivity:	None known
Chemical Stability:	Stable under r
Possibility of Hazardous Reactions:	None anticipa
Conditions to avoid:	Heat.
Incompatibility:	None known
Hazardous Decomposition:	Incomplete co

Stable under normal conditions None anticipated Heat. None known Incomplete combustion may release carbon monoxide

## SECTION 11 – TOXICOLOGICAL INFORMATION

## Primary routes of exposure and Symptoms

Inhalation:	May cause respiratory tract, nose, and throat irritation. Symptoms may include headache, nausea, dizziness, drowsiness, and confusion.
Ingestion:	May cause irritation of the mouth, throat, and stomach. Can target organs if large quantities are ingested.
Skin Contact:	May cause skin irritation or drying of skin.
Eye Contact:	Causes eye irritation.

Delayed and immediate effects and also chronic effects from short- and long-term exposure Acute Toxicity by Component:

Titanium Dioxide	
LD50 Oral:	>10,000 mg/kg (Rat)
LD50 Dermal:	>10,000 mg/m <sup>3</sup> (Rabbit)
LC50 Inhalation (Dust):	>6.82 mg/L (Rat, 4 hr)

**Chronic Toxicity:** 

Chemical Na	me	CAS No.	Weight%	IARC	NTP	ACGIH
Titanium Diox	ide*	13463-67-7	0-20%	2B - Possibly Carcinogenic to Humans		A4 - Not classifiable as human carcinogen

\*The IARC has classified titanium dioxide as possibly carcinogenic to humans (2B) but have also concluded that "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint." Titanium Dioxide is not classified as a carcinogen by NTP, OSHA, or the EPA.

SECTION 12 – ECOLOGICAL DATA			
Ecotoxicity:	No information available		
Persistence and Degradability:	No information available		
<b>Bioaccumulative Potential:</b>	No information available		
Mobility in Soil: No information available			
<b>Other Adverse Effects:</b>	No information available		
SECTION 13 – DISPOSAL CONSIDERATIONS			
Waste Disposal Method:	Disposal should be made in accordance with federal, state, and local regulations		

SECTION 14 – TRANSPORT INFORMATION		
DOT	Not regulated	
ICAO / IATA	Not regulated	
IMDG / IMO	Not regulated	

# SECTION 15 – REGULATORY INFORMATION

## No Information Available

SECTION 16 – OTHER INFORMATION		
HMIS Ratings:		
Health:	1	
Flammability:	0	
Reactivity:	0	
NFPA Ratings:		
Health:	1	
Flammability:	0	
Reactivity:	0	

Disclaimer: To the best of our knowledge, this information is accurate. However, we do not guarantee its accuracy and cannot be liable for any damages actual and consequential which might result from reliance thereon.